

# TEXWRAP

Packaging Systems

*"Speed, Flexibility, Dependable Performance"*

## 2010 | 2 BELT SIDE SEAL WITH PNEUMATIC HEAD

This intermittent two belt system is a compact wrapper with big capacity, capable of wrapping anything from a deck of cards to a toolbox to a bundle of wood flooring. Designed to run products up to 10" high x 20" wide x infinite length at film speeds up to 100 feet per minute.



MADE IN U.S.A



  
**AVERO**  
**PACKAGING CORPORATION**  
*Flexible Packaging – Machinery & Materials*  
**800-946-2837**

## Features, Functions & Benefits

- Large Product size capacity
- Comes standard with "UHS" Texwrap sideseal
- Bolt on film folder
- Maximum Film capacity: 32" CF
- Built in flexibility; wrapper can run with a variety of in-feed configurations.
- Easy change over "Tool-less" set up
- Touchscreen with set-up product memory & machine diagnostics
- Upstream/Downstream handshaking, quick connect cable system for additional equipment
- Welded Tubular construction with powder coat finish
- Internal scrap take up with film break and take up reel alarms
- Inverter duty AC motors
- Sensorless vector AC drives
- High performance AC inverter duty motors

| <b>Machine Specifications</b> | <b>Model 2010</b>  |
|-------------------------------|--|
| Maximum package size          | 10"H x 20"W x infinite length<br>(Maximum dimensions cannot be combined) |
| Minimum package size          | 4"L x 2"W (standard)<br>2"L x 2"W (with closing conveyor)                |
| Conveyor width                | 20"  |
| Cross seal width              | 24"  |
| Cross seal drive              | Pneumatic  |
| Max Film Width                | 32" CF   |
| Electrical Requirements       | 208/240 Vac, 1phase, 18/15 Amps  |
| Air Requirements              | 80 PSI, 5 CFM  |
| Conveyor Height               | 32" to 37"   |
| Maximum Film Speed            | 100 FPM  |
| Operator Control Panel        | Color Touch Screen   |

